


(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 January 2004 (15.01.2004)

PCT

(10) International Publication Number
WO 2004/006531 A1

(51) International Patent Classification⁷: **H04L 29/06**,
12/56

(21) International Application Number:
PCT/EP2003/007138

(22) International Filing Date: 3 July 2003 (03.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02 015 204.7 8 July 2002 (08.07.2002) EP

(71) Applicant (for all designated States except US): **SONY
INTERNATIONAL (EUROPE) GMBH** [DE/DE]; Kem-
perplatz 1, 10785 Berlin (DE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **SPALINK, Gerd**

[DE/DE]; Advanced Technology Center Stuttgart, Sony In-
ternational (Europe) GmbH, Heinrich-Hertz-Str. 1, 70327
Stuttgart (DE). **HÖFFLINGER, Jens** [DE/DE]; Advanced
Technology Center Stuttgart, Sony International (Europe)
GmbH, Heinrich-Hertz-Str. 1, 70327 Stuttgart (DE).

(74) Agent: **MÜLLER, Frithjof, E.**; Müller . Hoffmann &
Partner, Innere Wiener Strasse 17, 81667 München (DE).


(81) Designated States (*national*): CN, JP, US.

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: **CONVERGENCE LAYERS FOR NETWORK DEVICES AND METHOD FOR TRANSMITTING DATA TRAFFIC**



(57) Abstract: A network device for an ad-hoc established device network is described, which comprises a content detection layer for detecting the content type of external traffic received by said network device. According to the content type, the external traffic is routed to a content-specific convergence layer dedicated to handling the respective content type. Said content-specific convergence layers exchange network traffic with other network devices via content-specific connections that are suited to the requirements of the respective content type. On the part of a target network device, the received data stream can be routed to any external protocol. Thus, the device network allows interoperability between different external networking protocols.

BEST AVAILABLE COPY

DT15 Rev. PCT/PTO 07 JAN. 2005

**Convergence Layers for Network Devices and
Method for Transmitting Data Traffic**

The invention is related to a network device for use in an ad-hoc established device network, to a device network, and to a method for transmitting data traffic via a device network.

For a variety of home multimedia applications and business applications, it is important to establish networks, preferably wireless networks, for exchanging data and messages between different devices that are part of the network. In a typical business application scenario, a mobile terminal gets services over a fixed corporate or public infrastructure. In an exemplary home application scenario, a low-cost and flexible networking is supported to interconnect wireless digital consumer devices.

The ETSI Project BRAN (Broadband Radio Access Networks) has defined the standard HiperLAN (High Performance Radio Local Area Network), which provides high-speed multimedia communications between different broadband core networks and mobile terminals. HiperLAN/2 provides a flexible platform for a variety of business and home applications that can support a set of bit rates up to 54 Mbit/s. The HiperLAN/2 standard is an example how data can be transmitted between different devices in a wireless network. The invention is not limited to wireless networks according to the HiperLAN/2 standard, though. The invention is not limited to wireless networks. It can also be applied in wired networks.

A typical device network comprises several devices, with one of the devices acting as a controller that controls the other devices that act as mobile terminals. When different devices are brought within reach of each other, they start exchanging messages and establish a so-called ad-hoc network, with one of the devices assuming the control functionality.

In section 6.2 of ETSI BRAN HiperLAN2 Standard Spec: DLC home extension (ETSI TS 101 761-4 V1.3.2 (2002-01)), it is described how multiple convergence layers supporting different external networking standards can be active simultaneously within one wireless local area network.

- 2 -

1 It is an object of the invention to provide a network device and a method for routing data traffic of an external networking protocol through a local area network, whereby interoperability between different external networking technologies is supported.

5 The object of the invention is solved by a network device according to claim 1, by a device network according to claim 13, and by a method for transmitting data traffic via a device network according to claim 21. A computer program product according to the present invention is defined in claim 24 and a computer readable storage medium is defined in claim 25.

10 According to the invention, the network device for a device network comprises a content detection layer for detecting the content type of external traffic received by said network device. In dependence of the detected content type, said external traffic is passed to a content-specific convergence layer that is dedicated to handling the respective content type. Furthermore, the network device comprises a set of content-specific convergence layers, which exchange network traffic with other network devices of said device network via content-specific connections. Said content-specific connections are suited to the requirements of the respective content type.

15 In prior art solutions, external traffic received by a network device has been passed, according to the protocol of said external traffic, to a protocol-specific convergence layer. For example, IEEE 1394 data traffic has always been handled by a IEEE 1394-specific convergence layer, and Ethernet traffic has been handled by an Ethernet-specific convergence layer. The respective convergence layer has been responsible for transmitting the external traffic to its respective target network device, whereby the connection for transmitting the external traffic within the device network has been set up according to said external network.

20 According to the invention, when external traffic is received by a network device, the content type of said external traffic is detected by a content detection layer. For example, it might be detected that the external traffic is "packet-based data traffic". Alternatively, said external traffic might be "real-time critical data traffic", for example an audio or video data stream. When the content type has been detected, the received data traffic is pas-

1 sed to a convergence layer that is specific for said type of content. Thus, in-
stead of protocol-specific convergence layers, content-specific convergence
layers are used for setting up and releasing connections to other network
5 devices within the network, and for transmitting data traffic within the de-
vice network. The content specific connections that are built up by the con-
tent-specific convergence layers are suited to the requirements of the re-
spective content type.

10 The invention is based on the fact that the requirements for a data trans-
mission within a device network do not depend on the protocol of the exter-
nal traffic in the first place. It is possible to transmit packet-based data
traffic via a IEEE 1394 interface (IPover1394), though the standard IEEE
1394 is mostly used for the transmission of video data streams. Vice versa,
15 it is also possible to transmit real-time critical data via an IP network,
which is typically used for packet-based data transmission. The require-
ments for a data transmission within the device network depend in the first
place on the content type of the external traffic. The requirements imposed
by the content type define the parameters of the data connection that is
20 established between the source network device and the target network de-
vice. For example, a real-time critical video data stream requires that the
transmission delay never exceeds a predefined threshold, and that a fixed
bandwidth is permanently available for said data transmission. Generally,
there are no such restrictive requirements for packet-based data transmis-
sion.

25 According to the invention, for each content type, a specific convergence
layer is provided, which handles data streams of said content type ac-
cording to the content-specific requirements. The content-specific convergence
layers are responsible for establishing and releasing content-specific con-
30 nections within the device network, and for transmitting the respective ex-
ternal data traffic within the device network.

35 Within the network, the external traffic is transmitted from the source net-
work device, which has received said traffic from an external network, to a
target network device. On the part of the target network device, the arriving
data stream is taken care of by a corresponding convergence layer that is
responsible for the respective content type. To said target network device,

1 any external network may be connected. The convergence layer on part of
the target network device doesn't have to route the traffic to the external
protocol said traffic has emanated from. Instead, the received data traffic
may be mapped to any external protocol that is able to accept the respective
5 content type. For example, a video data stream emanating from a IEEE
1394 interface can be mapped, after it has been transmitted within the device
network, to a IEEE 1394 interface again. Alternatively, the video data
stream can also be mapped, on part of the target network device, to an IP
interface. This kind of data exchange between different external networking
10 technologies has not been possible in the prior art. The inventive concept of
content-specific convergence layers allows for an interoperability between
different external networking standards. In case two completely different
external network protocols can handle the same content type, it is possible
to receive external traffic of a first external protocol, route said traffic
15 through the device network, whereby an internal protocol is used, and map
the traffic, on the part of the receiving network device, to a second external
protocol. The device network can be seen as an adapting means for adapting
a first kind of external traffic to a second kind of external traffic.

20 One advantage of the inventive solution is that the available bandwidth of
the device network is used more effectively by allowing access to different
traffic types. Another advantage is that new networking technologies and
traffic types can be integrated easily into the existing convergence layer
architecture. Due to the generic design of the relevant modules, large
25 amounts of existing code can be reused in the process of the integration.

Preferably, one of said content types is real-time critical data, whereby said
set of content-specific convergence layers comprises a convergence layer
dedicated to handling real-time critical data. When real-time critical data,
30 for example an audio or video data stream, is transmitted from a first network
device to another network device of the device network, the following
requirements have to be fulfilled: First of all, transmission delays that exceed
a certain amount are not acceptable. Furthermore, for the transmission
of a real-time critical data stream, a certain bandwidth has to be permanently
35 available in order to allow for a continuous transmission of said
data stream. A convergence layer dedicated to handling real-time critical
data can set up content-specific connections within the device network that

1 allow to fulfil the above-mentioned requirements.

Further preferably, one of said content types is packet-based data, whereby said set of content-specific convergence layers comprises a convergence
5 layer dedicated to handling packet-based data. When regular packet-based data traffic has to be transmitted within the device network, there are no specific requirements concerning the transmission delay and available bandwidth as there are in case of real-time critical data. A convergence lay-
10 er dedicated to handling packet-based data will therefore set up a content-specific connection for the transmission of said data, whereby the available network resources are used in a more flexible way. In particular, it is not necessary to reserve a predefined bandwidth for the transmission of said packet-based data.

15 According to a preferred embodiment of the invention, said external traffic is at least one of Ethernet traffic, IEEE 1394 traffic, UMTS traffic or PPP traffic. The Ethernet protocol is the major protocol for accessing the inter-
net. IEEE 1394 is the most common standard for data exchange between audio and video devices and allows for large transmission bit rates. UMTS
20 is an example for a third generation mobile communications protocol, and PPP (point-to-point protocol) permits to establish point-to-point connections between two devices. Thus, the network device can be connected to a large range of current networking technologies simultaneously.

25 Preferably, said network device comprises hardware connectivity for at least one of Ethernet traffic, IEEE 1394 traffic, UMTS traffic or PPP traffic. Data packets received via said hardware connections are converted into the internal network protocol of the device network. Vice versa, data packets of the internal network protocol received from other network devices are con-
30 verted into data packets of the external networking technology. Then, these data packets are sent to the external network via said hardware connection.

Preferably, said network device is an access point of said device network.
35 The task of an access point is to provide access to different external networking technologies and networking services, for example to the internet. Therefore, the access points should be equipped with multiple content-spe-

1 cific convergence layers in the first place, because said access points have to handle different kinds of data traffic received from various external networks.

5 According to a preferred embodiment of the invention, said content detection layer analyses if said Ethernet traffic is real-time critical traffic, e.g. in connection with RTP, RTCP, RSVP, or RTSP traffic, whereby in case said Ethernet traffic is real-time critical, it is passed to a convergence layer dedicated to handling real-time critical data. Each data packet of Ethernet
10 data traffic comprises type field information indicating the content of the respective Ethernet data packet. Thus, the content detection layer can easily determine if said Ethernet traffic is real-time critical or not. If the result of analysing the type field information is that said Ethernet traffic is real-time critical, it is passed to the convergence layer that handles real-time critical data. Therefore, in the case of Ethernet packets, the detection
15 of the respective content type can be implemented in a very simple way.

Further preferably, said content detection layer analyses if said Ethernet traffic is not real-time critical traffic, i.e. of some other protocol type and
20 thus packet-based traffic, whereby in case said Ethernet traffic is not real-time critical, it is passed to a convergence layer dedicated to handling packet-based data. The type field information of an Ethernet packet indicates the content of said data packet. The content detection layer can easily detect whether the received Ethernet traffic is packet-based data traffic or
25 not. Packet-based data traffic is passed to a convergence layer dedicated to handling this content type.

Preferably, said content detection layer analyses if said IEEE 1394 traffic is packet-based data traffic, whereby in case said IEEE 1394 traffic is packet-based data traffic, it is passed to a convergence layer dedicated to handling
30 packet-based data. Further preferably, said content detection layer analyses if said IEEE 1394 traffic is real-time critical data traffic, whereby in case said IEEE 1394 traffic is real-time critical data traffic, it is passed to a convergence layer dedicated to handling real-time critical data. Via a IEEE
35 1394 interface, either real-time critical IEEE 1394 data traffic or packet-based data traffic (IPover1394) can be transmitted. Also with regard to 1394 traffic, it is possible to analyse at low expense the respective content

- 1 type. According to the content type, the IEEE 1394 traffic is either passed to a convergence layer for handling real-time critical data, or to a convergence layer for handling packet-based data traffic.
- 5 According to a preferred embodiment of the invention, said content-specific convergence layers comprise a common part, which segments data packets of said external traffic into a multitude of corresponding data packets of said device network's internal protocol, and which reassembles data packets of said device network's internal protocol into corresponding data packets of the respective external traffic. All the external networking technologies mentioned so far have one thing in common: They use variable size data packets which comprise more bytes than the rather small LCH (Long Transport Channel) data packets used within the HiperLAN/2 network, which only comprise 48 bytes. Therefore, data packets of the external protocol have to be segmented into a multitude of HiperLAN/2 data packets. Data packets received from the HiperLAN/2 network have to be reassembled into the data packets of the respective external protocol. Instead of providing each one of the convergence layers with a unit for segmenting and reassembling data packets, this task is accomplished, for all the convergence layers, by the common part of the convergence layers. The common part segments data packets arriving from the respective external network into a multitude of data packets of the internal network's protocol, and reassembles data packets of the internal protocol into variable size data packets of the respective external protocol. By implementing said common part, the structure of the content-specific convergence layers can be simplified. Another advantage is that in case a new convergence layer for another content type is to be implemented, programming said new convergence layer is simplified, because the functionality of the common part can be used.
- 30 Preferably, said content-specific convergence layers are operable to be used simultaneously within the same device network. Therefore, a network device can simultaneously handle data streams of different content type.
- 35 According to the invention, a device network is set up, which comprises at least one network device with a content detection layer, and with a set of content-specific convergence layers as described above.

1 Preferably, content-specific connections are set up and released between
the network devices of said device network, whereby a content-specific con-
nection is set up between a content-specific convergence layer of a first
5 content-specific convergence layer of a second network device which sup-
ports the same content type. Between convergence layers supporting the
same content type, a connection can be established. As soon as the connec-
tion is established, any amount of data packets can be transmitted between
the two content-specific convergence layers. By defining content-specific
10 connections for handling data transmissions within the ad-hoc established
device network, it is possible to define the parameters of the data transmis-
sion according to the content type, and to choose these parameters accor-
ding to the desired bandwidth, error handling, etc.

15 According to a preferred embodiment of the invention, the external traffic
exchanged with said content-specific convergence layer of said first network
device may be of a different kind than the external traffic exchanged with
said content-specific convergence layer of said second network device. On
the part of the target network device, the received data stream may be for-
20 forwarded to any external protocol that is willing and able to accept the re-
spective content type. The data stream that has been transmitted via the
ad-hoc established device network can thus be distributed to an external
network that is different from the external network the data stream has
emanated from. Data traffic from a first external networking technology
25 may be routed to a second external networking technology. The device net-
work serves as an adapting means for all kinds of network traffic. This
makes the device network, preferably the wireless LAN technology, much
more powerful and flexible.

30 Preferably, in case said content-specific connection is for a content type
which requires a quality of service feature, a fixed bandwidth is reserved
for said content-specific connection. The "quality of service" feature is a
well-known feature for the transmission of video data. A certain bandwidth
is reserved for the transmission of the video data stream, and thus, a cer-
35 tain quality of service (QoS) is guaranteed. When transmitting video data
streams or any other data traffic supporting the quality of service feature
via a device network, it is possible to set up the connection in a way that

1 the quality of service feature is supported.

Further preferably, for each content-specific connection, the content type supported by said content-specific connection is registered. Any traffic
5 transmitted via the content-specific connection can be passed, on the part of the target network device, to the corresponding content-specific convergence layer dedicated to handling the respective content type.

Further preferably, said device network is a wireless local area network (WLAN), and in particular a HiperLAN/2 network. HiperLAN/2 is a European standard for wireless local area networks.

According to a preferred embodiment of the invention, the exchange of control messages and data packets between different network devices of said
15 device network is effected according to a TDMA transmission scheme. Preferably, a set of time slots of said TDMA transmission scheme may be reserved for a certain content-specific connection. By doing this, a predefined transmission capacity can be assigned to a certain connection. This is one way of realizing the above-mentioned quality of service feature.

20 Further features and advantages of preferred embodiments according to the present invention will be explained below in conjunction with the accompanying drawings, in which

25 **Fig. 1** shows how different networking technologies interact in order to provide a networking environment;

Fig. 2 shows a wireless local area network comprising two network devices according to the prior art;

30 **Fig. 3** shows a wireless local area network, whereby both real-time critical and regular packet-based data streams are transmitted via the wireless LAN;

35 **Fig. 4** depicts the structure of the protocol stack for the HiperLAN/2 standard; and

1 **Fig. 5** shows how higher layer packets, for example Ethernet packets, are mapped onto layers of the HiperLAN/2 standard.

5 Fig. 1 shows the interplay of different network protocols in a networking environment. The Internet 1 provides the backbone for all kinds of data exchange services. In an office environment 2, servers 3 and access points 4 for wireless data transmission are connected by means of the Ethernet protocol. In order to establish wireless local area networks for connecting mobile terminals 5 to said access points 4, the Ethernet protocol can be converted into a suitable protocol for wireless data transmission, e.g. into the HiperLAN/2 protocol. Also in a home environment 6, the HiperLAN/2 protocol is used for establishing an ad-hoc device network for exchanging data between audio and video devices 7, personal computers 8, organizers 9, etc. In the field of mobile communication 10, the standards GPRS and UMTS are used for exchanging data packets between mobile devices 11 and base stations 12, and for accessing the Internet 1. For small distances, the Bluetooth protocol is used. For all these applications, the Internet Service Provider 13 provides a high-bandwidth backbone 14 and all kinds of data exchange services (email, world wide web, WAP, FTP, etc.).

20

25 In Fig. 2, a wireless local area network of the prior art is shown. The wireless local area network comprises an access point 15, which acts as a central controller for the network, and a mobile terminal 16. The mobile terminal 16 exchanges data packets with the access point 15 via the HiperLAN/2 protocol. The access point 15 comprises hardware connectivity for an external network protocol, the Network Type 1 (18), e.g. for the Ethernet. Furthermore, the access point 15 comprises a Network Type 1 convergence layer 17 for converting data packets received via the Network Type 1 (18) into the HiperLAN/2 standard (19), and for converting data packets received via the HiperLAN/2 (19) into the Network Type 1 standard (18).

30

35 In Fig. 3, a device network comprising four network devices with content-specific convergence layers are shown. An Ethernet device 20, which is connected to the Ethernet via IP (Internet Protocol), is part of the device network 21. Preferably, the device network is a wireless local area network (LAN), in particular according to the HiperLAN/2 standard. The Ethernet device 20 can receive regular IP traffic 22 from the Internet. Regular

1 packet-based IP traffic is transmitted according to protocols aside from those that are explicitly used for real-time critical data (e.g. RTP, RTCP, RSVP, or RTSP). The Ethernet device 20 can also receive real-time critical data traffic 23 via the Ethernet interface, e.g. a video data stream. For the transmission of real-time critical data traffic via an IP network, currently the protocols RTP (Real-Time Protocol), RTCP (Real-Time Control Protocol), RSVP (resource ReSerVation Protocol), and RTSP (Real-Time Streaming Protocol) are used.

10 Let us assume that real-time critical video data stream 23 emanating from the Ethernet device 20 shall be transmitted via the device network 21 to other network devices. The video data stream 23 is first passed to a content detection and routing layer 24, and said content detection and routing layer 24 detects that the arriving data stream utilizes one of the real-time critical protocol types. Therefore, the content type is identified as "real-time critical data traffic". Accordingly, the real-time critical data stream is forwarded to a convergence layer 25 dedicated to handling "real-time critical data traffic". Besides the convergence layer 25, other content-specific convergence layers exist, e.g. the convergence layer 26, which is dedicated to handling "packet-based data traffic".

The content-specific convergence layer 25 establishes a content-specific connection with a corresponding convergence layer on the part of the target network device. In case real-time critical data traffic has to be transmitted, the convergence layer 25 reserves a certain predefined bandwidth when establishing the connection to the respective target network devices. Then, the IP data packets of the real-time critical data traffic are segmented into a set of corresponding data packets of the internal protocol of the device network 21. This task can be carried out by a separate module which is a common part of the content-specific convergence layers 25 and 26. In case the device network 21 is a HiperLAN/2 network, 48 byte packets of the type LCH (Long Transport Channel) are used within the device network 21.

Now, the video data stream 23 of our example is transmitted via the device network 21 to the respective target network devices. There, the arriving data packets are forwarded to a content detection and routing layer 27. In case a target network device, e.g. a IEEE 1394 device 28 or an Ethernet de-

- 12 -

1 vice 29, has indicated that it is willing to accept a respective traffic type,
the content detection and routing layer 27 forwards the received data stream
the content detection and routing layer 27 forwards the received data stream
to the respective target device. In case the Ethernet device 29 has indicated
that it is willing to accept the video data stream, the received video
5 data stream is routed (30) to the Ethernet device 29. There, the short LCH
data packets are reassembled to build IP packets, and the real-time critical
video data stream is again converted into an appropriate protocol for real-
time critical data. The video data stream can then be forwarded to the IP
network to which the Ethernet device 29 is connected.

10 So far, it has been described how the video data stream 23, which is an IP
data stream, is converted to the device network's internal protocol and
transmitted via said device network to another Ethernet device 29. The video
data stream 23, which has emanated from an IP network, doesn't have
15 to be routed to an Ethernet device, though. The content detection and routing
layer 27 can also route the received real-time critical data stream to
the IEEE 1394 device 28 when the IEEE 1394 device 28 requests it. On
part of the IEEE 1394 device 28, the LCH data packets of the internal protocol
are reassembled into a video data stream 31 according to the IEEE
20 1394 protocol. The real-time critical video data stream can then be forwarded
to the IEEE 1394 network to which the IEEE 1394 device 28 is connected.
The inventive concept of content-specific convergence layers and content-specific
routing allows to transform a real-time critical IP data stream
into an IEEE 1394 data stream. Besides that, it is also possible to transmit
25 the real-time critical video data stream 23 emanating from the Ethernet to
both an Ethernet device 29 and a IEEE 1394 device 28.

In the following, a second example will be discussed. On the part of the
Ethernet device 20, regular IP traffic 22 is received from the Internet. The
30 regular IP traffic is passed to the content detection and routing layer 24,
which detects that the content type is "packet-based data traffic", which is
not real-time critical. The regular IP traffic 22 is then passed to the convergence
layer 26, which is dedicated to handling "packet-based data traffic".
The IP packets are segmented into the LCH data packets used within the
35 HyperLAN/2 network. A connection is set up within the device network 21,
and the data traffic is transmitted to the content detection and routing layer
27. From there, the traffic can be routed to the Ethernet device 29. The

1 received packets of the internal protocol are reassembled into IP packets,
and the IP data stream 32 is obtained.

5 Alternatively or additionally, the data traffic can be routed from the content
detection and routing layer 27 to the IEEE 1394 device 28. There, the recei-
ved packets of the internal protocol are reassembled into data packets ac-
cording to the IEEE 1394 standard. Though the IEEE 1394 standard is in-
tended for the transmission of audio and video data streams in the first
10 place, it is also possible to transmit IP data packets via an IEEE 1394 in-
terface. This is called "IPover1394". Such an "IPover1394" data stream 33
is obtained on the part of the IEEE 1394 device 28.

Both real-time critical data streams and regular packet-based data traffic
can also emanate from a IEEE 1394 device 34 that is connected to an ex-
15 ternal IEEE 1394 network. The video data stream 35 can be transmitted
from the IEEE 1394 device 34 via the convergence layer 25 and the device
network 21 to the IEEE 1394 device 28, or to the Ethernet device 29, or to
both said devices. The IPover1394 data traffic 36 is passed to the conver-
gence layer 26, which handles packet-based data traffic. Via the device net-
20 work 21, the data traffic is routed to the IEEE 1394 device 28, or to the
Ethernet device 29, or to both said devices.

In Fig. 4, the so-called protocol stack for the HiperLAN/2 standard is
shown. The bottom layer is the Physical Layer 37, which deals with the mo-
25 dulation type and the actual data transmission. The next layer is the Medi-
um Access Control (MAC) 38, which is part of the Data Link Control Layer
(DLC) 39. The MAC 38 schedules the data for transmission. A TDMA (Time
Division Multiple Access) frame with time slots of 2 ms is used, and the
MAC 38 assigns time slots of the TDMA frame to the various connections
30 within the HiperLAN/2 network. The TDMA frame generated by the MAC 38
is the typical transmission standard in the HiperLAN/2 protocol. The Data
Link Control Layer 39 further comprises an Error Control functionality 40.
Furthermore, the Data Link Control Layer 39 comprises a Radio Link Con-
trol Sublayer (RLC) 41.

35

The highest layers of the HiperLAN/2 standard are the convergence layers
42, which comprise a content type detection and routing layer 43, a set of

- 14 -

1 content-specific convergence layers 44, 45, and a common part 46 of said
convergence layers. The content type detection and routing layer 43 de-
tects the content type of arriving data traffic and passes said traffic to a
corresponding content-specific convergence layer. The convergence layer
5 44 handles packet-based data traffic, whereby the convergence layer 45
handles real-time critical data traffic.

The common part 46 segments the variable size data packets of the re-
spective external protocol into a multitude of data packets according to
10 the HiperLAN/2 standard. Besides that, the common part 46 converts Hi-
perLAN/2 packets into data packets of an external protocol by reassem-
bling the HiperLAN/2 packets.

The respective hardware connectivity is addressed by means of drivers 47,
15 48, 49. The convergence layer 47 is responsible for handling the PPP
(point-to-point) protocol, which is an external protocol used for point-to-
point connections. The driver 48 supports the IEEE 1394 protocol, and
the driver 49 supports the Ethernet protocol.

20 In Fig. 5, it is shown how higher layer packets, for example Ethernet pak-
kets, are mapped onto layers of the HiperLAN/2 standard. Again, the Phy-
sical Layer PHY is the bottom layer, and a PHY burst 52 comprising se-
veral Long Transport CHannel Packets (LCH) is shown. At the Data Link
Control Layer (DLC), a Long Transport CHannel Packet (LCH) 53 is divided
25 into a header 54, a DLC SDU 55, and a Cyclic Redundancy Check (CRC)
56. At the Convergence Layer (CL), the DLC SDU 55 is divided into 12 bits
of flags (57) and 384 bits or 48 bytes of Payload (58). A higher layer
packet, e.g. an Ethernet packet 59, is segmented into a multitude of these
48 bytes packets 58, 60, which are transmitted as LCH packets according
30 to the HiperLAN/2 standard.

1

Claims

1. Network device for a device network, **characterized by**
- a content detection layer (24, 43) for detecting the content type of external traffic received by said network device, and for passing said external traffic, in dependence of the detected content type, to a content-specific convergence layer (25, 26, 44, 45) dedicated to handling the respective content type, and
- a set of content-specific convergence layers (25, 26, 44, 45), which exchange network traffic with other network devices (28, 29) of said device network (21) via content-specific connections, whereby said content-specific connections are suited to the requirements of the respective content type.
2. Network device according to claim 1, **characterized in that** one of said content types is real-time critical data, whereby said set of content-specific convergence layers comprises a convergence layer dedicated to handling real-time critical data.
3. Network device according to claim 1 or 2, **characterized in that** one of said content types is packet-based data, whereby said set of content-specific convergence layers comprises a convergence layer dedicated to handling packet-based data.
4. Network device according to anyone of the preceding claims, **characterized in that** said external traffic being at least one of Ethernet traffic, IEEE 1394 traffic, UMTS traffic or PPP traffic.
5. Network device according to anyone of the preceding claims, **characterized in that** said network device comprises hardware connectivity for at least one of one of Ethernet traffic, IEEE 1394 traffic, UMTS traffic or PPP traffic.
6. Network device according to anyone of the preceding claims, **characterized in that** said network device is an access point of said device network.

- 16 -

1 7. Network device according to anyone of the preceding claims, **characterized in that** said content detection layer analyses if said Ethernet traffic is real-time critical traffic, whereby in case said Ethernet traffic is real-time critical, it is passed to a convergence layer dedicated to handling
5 real-time critical data.

8. Network device according to anyone of the preceding claims, **characterized in that** said content detection layer analyses if said Ethernet traffic is not real-time critical traffic, whereby in case said Ethernet traffic is
10 not real-time critical, it is passed to a convergence layer dedicated to handling packet-based data.

9. Network device according to anyone of the preceding claims, **characterized in that** said content detection layer analyses if said IEEE 1394
15 traffic is packet-based data traffic, whereby in case said IEEE 1394 traffic is packet-based data traffic, it is passed to a convergence layer dedicated to handling packet-based data.

10. Network device according to anyone of the preceding claims, **characterized in that** said content detection layer analyses if said IEEE 1394
20 traffic is real-time critical data traffic, whereby in case said IEEE 1394 traffic is real-time critical data traffic, it is passed to a convergence layer dedicated to handling real-time critical data.

25 11. Network device according to anyone of the preceding claims, **characterized in that** said content-specific convergence layers comprise a common part, which segments data packets of said external traffic into a multitude of corresponding data packets of said device network's internal protocol, and which reassembles data packets of said device network's internal
30 protocol into corresponding data packets of the respective external traffic.

12. Network device according to anyone of the preceding claims, **characterized in that** said content-specific convergence layers are operable to be
35 used simultaneously within the same device network.

13. Device network, comprising at least one network device according to

1 anyone of claims 1 to 12.

14. Device network according to claim 13, **characterized in that** content-specific connections are set up and released between the network devices of said device network, whereby a content-specific connection is set up between a content-specific convergence layer of a first network device which supports a certain content type, and a respective content-specific convergence layer of a second network device which supports the same content type.

10

15. Device network according to claim 13 or 14, **characterized in that** the external traffic exchanged with said content-specific convergence layer of said first network device may be of a different kind than the external traffic exchanged with said content-specific convergence layer of said second network device.

15

16. Device network according to anyone of claims 13 to 15, **characterized in that** in case said content-specific connection is for a content type which requires a quality of service feature, a fixed bandwidth is reserved for said content-specific connection.

20

17. Device network according to anyone of claims 13 to 16, **characterized in that** for each content-specific connection, the content type supported by said content-specific connection is registered.

25

18. Device network according to anyone of claims 13 to 17, **characterized in that** said device network is a wireless local area network (WLAN), and in particular a HiperLAN/2 network.

30

19. Device network according to anyone of claims 13 to 18, **characterized in that** the exchange of control messages and data packets between different network devices of said device network is effected according to a TDMA transmission scheme.

35

20. Device network according to claim 19, **characterized in that** a set of time slots of said TDMA transmission scheme may be reserved for a certain content-specific connection.

- 18 -

- 1 21. Method for transmitting data traffic via a device network, **characteri-**
zed by the following steps:
- detecting a content type of external traffic arriving at the device network,
 - passing said external traffic, in dependence of the detected content type,
 - 5 to a content-specific convergence layer (25, 26, 44, 45) dedicated to hand-
ling the respective content type, and
 - transmitting network traffic to other network devices (28, 29) via content-
specific connections, whereby said content-specific connections are suited
to the requirements of the respective content type.
- 10 22. Method according to claim 21, **characterized in that** content-specific
connections are set up between two network devices before transmitting
said network traffic between said two network devices in accordance with
said content type.
- 15 23. Method according to claim 21 or 22, **characterized in that** after the
network traffic between said two network devices has been transmitted in
accordance with said content type, said content-specific connection betwe-
en said two network devices is released.
- 20 24. Computer program product comprising computer program means ad-
apted to perform the method steps as defined in anyone of claims 21 to 23
when being executed on a computer, a digital signal processor or the like.
- 25 25. Computer readable storage means, storing thereon a computer pro-
gram product according to claim 24.

30

35




Figure 1




Fig. 2
Prior Art




Figure 3




Figure 4




Figure 5

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP 03/07138

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H04L29/06 H04L12/56

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6 028 842 A (CHAPMAN ALAN STANLEY JOHN ET AL) 22 February 2000 (2000-02-22)	1-10, 12, 13, 16-25
Y	column 3, line 11 -column 6, line 30; figures 2, 3, 5, 6	11, 14
A	---	15
Y	WO 00 13436 A (NOKIA OY AB ;SODERLUND TOM (FI); MIKKONEN JOUNI (FI); ALA LAURILA) 9 March 2000 (2000-03-09) figures 8, 10	11, 14
X	EP 1 148 687 A (ERICSSON TELEFON AB L M) 24 October 2001 (2001-10-24) column 9, line 41 -column 9, line 54 column 12, line 6 -column 12, line 16; figures 1-7	1, 21, 24

	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

24 November 2003

Date of mailing of the international search report

02/12/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Olmos, J

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP 03/07138

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6 122 263 A (DAHLIN STEINAR ET AL) 19 September 2000 (2000-09-19) abstract column 2, line 43 -column 3, line 34 column 4, line 26 -column 4, line 34 column 6, line 57 -column 7, line 4; figures 1,2 ---	1,21,24
X	US 5 737 495 A (RICHARDSON JOHN W ET AL) 7 April 1998 (1998-04-07) abstract column 5, line 25 -column 5, line 60; figures 2B,3 ---	1,21,24
A	EP 0 971 518 A (NIPPON ELECTRIC CO) 12 January 2000 (2000-01-12) page 3, line 8 -page 3, line 56 page 17, line 33 -page 17, line 54; figures 7,8,10 ---	1,21,24
A	WO 02 17565 A (AFTELAK STEPHEN BASIL ;BADEN CHARLOTTE CATHERINE (GB); GIBBS JONAT) 28 February 2002 (2002-02-28) page 1, line 1 -page 7, line 11 ---	1,21,24
A	WO 01 22666 A (ERICSSON TELEFON AB L M) 29 March 2001 (2001-03-29) abstract -----	3

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 03/07138

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 6028842	A	22-02-2000	WO 9828938 A1 WO 9828939 A1 EP 0954943 A1 JP 2000508145 T US 6023456 A	02-07-1998 02-07-1998 10-11-1999 27-06-2000 08-02-2000
WO 0013436	A	09-03-2000	AU 5983299 A CN 1324537 T WO 0013436 A2 EP 0982909 A2 EP 1108316 A2 GB 2341059 A JP 2002524941 T	21-03-2000 28-11-2001 09-03-2000 01-03-2000 20-06-2001 01-03-2000 06-08-2002
EP 1148687	A	24-10-2001	EP 1148687 A1 AU 5630801 A WO 0182558 A2 EP 1275235 A2	24-10-2001 07-11-2001 01-11-2001 15-01-2003
US 6122263	A	19-09-2000	AU 8045698 A CN 1260094 T EP 0988742 A1 JP 2002503419 T WO 9857482 A1	30-12-1998 12-07-2000 29-03-2000 29-01-2002 17-12-1998
US 5737495	A	07-04-1998	US 5933835 A	03-08-1999
EP 0971518	A	12-01-2000	JP 3225924 B2 JP 2000032056 A CA 2277229 C EP 0971518 A2 US 6415313 B1	05-11-2001 28-01-2000 09-09-2003 12-01-2000 02-07-2002
WO 0217565	A	28-02-2002	GB 2366119 A AU 9174001 A WO 0217565 A2 EP 1312184 A2	27-02-2002 04-03-2002 28-02-2002 21-05-2003
WO 0122666	A	29-03-2001	SE 521463 C2 AU 7565700 A WO 0122666 A1 SE 9903390 A	04-11-2003 24-04-2001 29-03-2001 21-03-2001